MATERIAL SAFETY DATA SHEET West System Inc.

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: G5 Adhesive - Part A.

PRODUCT CODE:.....865

CHEMICAL FAMILY: Epoxy resin.

CHEMICAL NAME:..... Bisphenol-A based epoxy resin.

FORMULA: Not applicable.

MANUFACTURER: EMERGENCY TELEPHONE NUMBERS:

West System Inc. Transportation

102 Patterson Ave. CHEMTREC:800-424-9300 (U.S.)

Bay City, MI 48706, U.S.A. 703-527-3887 (International)

Phone: 866-937-8797 or 989-684-7286 Non-transportation

www.westsystem.com Poison Hotline:800-222-1222

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

<u>INGREDIENT NAME</u> <u>CAS # CONCENTRATION</u>

Bisphenol-A type epoxy resin 25085-99-8 > 50% Bisphenol-F type epoxy resin 28064-14-4 < 50%

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS Hazard Rating: Health - 2 Flammability - 1 Reactivity - 0

CAUTION. Moderate eye irritant. Moderate skin irritant. Possible skin sensitizer. Light-yellow liquid with mild odor and high viscosity.

PRIMARY ROUTE(S) OF ENTRY: Skin contact.

POTENTIAL HEALTH EFFECTS:

MSDS# 865A-05a Last Revised: 03JAN05

CHRONIC SKIN CONTACT: cause moderate irritation to the skin.	. May cause sensitization in susceptible individuals. May
EYE CONTACT:	May cause irritation.
INGESTION:	Low acute oral toxicity.
	Possible sensitization and subsequent allergic reactions ure is not likely to cause other adverse health effects.
MEDICAL CONDITIONS AGGRAVATED BY Pre-existing skin and respiratory disorders may be a and skin allergies may increase the chance of develo	aggravated by exposure to this product. Pre-existing lung
FIRST AID MEASURES:	
FIRST AID FOR EYES: seek medical advice.	Flush with plenty of water for at least 15 minutes and
FIRST AID FOR SKIN: soap and water.	Remove contaminated clothing. Wash contact area with
FIRST AID FOR INHALATION: medical attention.	Remove to fresh air. If effects occur and persist get
FIRST AID FOR INGESTION: necessary unless large quantities are ingested. Get	Do not induce vomiting. In general, no treatment is medical advice.
FIRE FIGHTING MEASURES:	
FLASH POINT:	> 200°F (TCC)
EXTINGUISHING MEDIA: chemical.	Water fog, alcohol foam, carbon dioxide (CO ₂) or dry
	Burning material will generate toxic fumes. Wear reathing apparatus. Cool fire-exposed containers with d.
ACCIDENTAL RELEASE MEASURES:	
SPILL OR LEAK PROCEDURES: Wear appropriate personal protective equipment. S Residual can be removed with safe, non-flammable	
HANDLING AND STORAGE:	
STORAGE TEMPERATURE (MIN./MAX):	40°F (4°C) / 120°F (49°C)
STORAGE: prevent loss of volatiles.	Store in cool, dry place with tightly closed container to

4.

5.

6.

7.

West System Inc. Page 3 of 6 G5 Adhesive - Part A

HANDLING PRECAUTIONS:	Ventilate work area.	Avoid skin contact.	Wash
thoroughly after using.			

8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

SKIN PROTECTION GUIDELINES:...... Wear liquid-proof, chemical resistant gloves (nitrile-butyl rubber, neoprene, butyl rubber or natural rubber) and full body-covering clothing.

RESPIRATORY/VENTILATION GUIDELINES:

General mechanical and local exhaust ventilation is sufficient for most operations. A NIOSH/MSHA approved respirator with an organic vapor cartridge may be used when adequate ventilation is not possible or when using heated product.

ADDITIONAL PROTECTIVE MEASURES:

Practice good caution and personal cleanliness to avoid skin and eye contact. Avoid skin contact when removing gloves and other protective equipment. Wash thoroughly after handling..

OCCUPATIONAL EXPOSURE LIMITS: Not established for product as whole. Refer to OSHA's Permissible Exposure Level (PEL) or the ACGIH Guidelines for information on specific ingredients.

9. PHYSICAL AND CHEMICAL PROPERTIES:

PHYSICAL FORM	Viscous liquid.
COLOR	Pale yellow.
ODOR	Mild.
BOILING POINT	> 400°F.
MELTING POINT/FREEZE POINT	No data.
pH	No data.
SOLUBILITY IN WATER	Slight.
SPECIFIC GRAVITY	1.15
BULK DENSITY	9.6 pounds/gallon.
VAPOR PRESSURE	
VAPOR DENSITY	U
% VOLATILE BY WEIGHT	< 1%

10. REACTIVITY:

STABILITY:	. Stable.
HAZARDOUS POLYMERIZATION:	. Will not occur.
INCOMPATIBILITIES: polymerization.	. Strong acids, bases, amines and mercaptans can cause
DECOMPOSITION PRODUCTS: produced when heated to decomposition.	. Carbon monoxide and carbon dioxide fumes may be

11. TOXICOLOGICAL INFORMATION:

No specific oral, inhalation or dermal toxicology data is known for this product. Specific toxicology information for a bisphenol-A based epoxy resin present in this product is indicated below:

 $\label{eq:control_co$

CARCINOGENICITY:

Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol-A. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that DGEBPA is carcinogenic. Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that DGEBPA is not classified as a carcinogen.

Epichlorohydrin, an impurity in this product (<25 ppm) has been reported to produce cancer in laboratory animals and to produce mutagenic changes in bacteria and cultured human cells. It has been established by the International Agency for Research on Cancer (IARC) as a probable human carcinogen (Group 2A) based on the following conclusions: human evidence – inadequate; animal evidence – sufficient. It has been classified as an anticipated human carcinogen by the National Toxicology Program (NTP).

12. ECOLOGICAL INFORMATION:

Prevent entry into sewers and natural waters. May cause localized fish kill.

Movement and Partitioning:

Bioconcentration potential is moderate (BCF between 100 - 3000 or Log Kow between 3 - 5).

Degradation and Transformation:

Theoretical oxygen demand is calculated to be 2.35 p/p. 20-day biochemical oxygen demand is < 2.5%.

Ecotoxicology:

Material is moderately toxic to aquatic organisms on an acute basis. LC_{50}/EC_{50} between 1 - 10 mg/L in most sensitive species.

13. <u>DISPOSAL CONSIDERATIONS:</u>

Incinerate, recycle (fuel blending) or reclaim may be preferred methods when conducted in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION:

D.O.T. SHIPPING NAME:	Not regulated by DOT.
TECHNICAL SHIPPING NAME:	
D.O.T. HAZARD CLASS:	
U.N./N.A. NUMBER:	Not applicable.
PACKING GROUP:	

15. <u>REGULATORY INFORMATION:</u>

OSHA STATUS:	Slight irritant; possible sensitizer.
	All components are listed on TSCA inventory.
SARA TITLE III:	1
SECTION 313 TOXIC CHEMICALS	None

STATE REGULATORY INFORMATION:

The following chemicals are specifically listed or otherwise regulated by individual states. For details on your regulatory requirements you should contact the appropriate agency in your state.

COMPONENT NAME

/CAS NUMBER	CONCENTRATION	STATE CODE
Epichlorohydrin 106-89-8	< 5ppm	¹CA, MA, PA, RI
Phenyl glycidyl ether 122-60-1	<5ppm	1CA

^{1.} These substances are known to the State of California to cause cancer or reproductive harm, or both.

16. OTHER INFORMATION:

REASON FOR ISSUE:	
PREPARED BY:	-
APPROVED BY:	G. M. House
TITLE:	Health, Safety & Environmental Manager
APPROVAL DATE:	
SUPERSEDES DATE:	January 5, 2004
MSDS NUMBER:	· · · · · · · · · · · · · · · · · · ·

Note: The Hazardous Material Indexing System (HMIS), cited in the Emergency Overview of Section 3, uses the following index to assess hazard rating: 0 = Minimal; 1 = Slight: 2 = Moderate; 3 = Serious; and 4 = Severe.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of West System Inc. The data on this sheet is related only to the specific material designated herein. West System Inc. assumes no legal responsibility for use or reliance upon these data.

MSDS# 865A-05a Last Revised: 03JAN05